

SOLAR N PLUS

N型双面组件

N-Type Bifacial Modules

SP-N16/144HG570-600W

600W最高组件功率输出
Maximum Power**23.2%**最高组件效率
Module Efficiency**0~+5W**组件功率公差
Power Tolerance

产品特性 PRODUCT CHARACTERISTICS

**更高发电增益**

Higher Power Generation Gain

**低热斑风险**

Low Hot Spot Risk

**自清洁能力**

Excellent Self-Cleaning Capability

**小倾角应用场景更优**

Superior Performance in Low-Tilt Applications

**更优的温度系数**

Lower Temperature Coefficient

**更优弱光响应**

Superior Low Irradiance Performance

认证 CERTIFICATION




- ISO 9001: 2015/质量管理体系 quality management system
- ISO 14001: 2015/环境管理体系 environment management system
- ISO 45001: 2018/职业健康安全管理体系 occupation health safety management system

保险 INSURANCE



线性功率保证 WARRANTY



材料工艺质保

Guarantee on product material and workmanship



线性功率质保

Linear power output warranty

**安徽旭合新能源科技有限公司 Solar N Plus New Energy Technology Co., LTD**

地址: 安徽省滁州市中新苏滁产业开发区建业路1号

Add: No.1 Jianye road, Suchu High-Tech Industrial Park, Chuzhou City, Anhui Province, China

电话 Tel: 0550-3012191

网址 web: www.solarnplus.com

电性能参数 ELECTRICAL CHARACTERISTICS (STC)

最大功率 Maximum Power (Pm)	W	570	575	580	585	590	595	600
功率公差 Power Tolerance	W				0~+5			
最佳工作电压 Maximum Power Voltage (Vm)	V	44.75	44.95	45.15	45.35	45.55	45.75	45.95
最佳工作电流 Maximum Power Current (Im)	A	12.74	12.79	12.85	12.90	12.96	13.01	13.06
开路电压 Open Circuit Voltage (Voc)	V	52.2	52.4	52.6	52.8	53.0	53.2	53.4
短路电流 Short Circuit Curren (Isc)	A	13.47	13.52	13.57	13.62	13.67	13.72	13.77
组件效率 Module Efficiency (ηm)	%	22.1	22.3	22.5	22.6	22.8	23.0	23.2

STC:AM=1.5, 辐照度 irradiance 1000W/m², 组件温度 module temperature 25°C

电性能参数 ELECTRICAL CHARACTERISTICS (NMOT)

最大功率 Maximum Power (Pm)	W	430	433	437	441	445	449	453
最佳工作电压 Maximum Power Voltage (Vm)	V	41.18	41.36	41.54	41.72	41.90	42.08	42.26
最佳工作电流 Maximum Power Current (Im)	A	10.42	10.47	10.52	10.57	10.62	10.67	10.72
开路电压 Open Circuit Voltage (Voc)	V	49.33	49.53	49.73	49.93	50.13	50.33	50.52
短路电流 Short Circuit Current (Isc)	A	10.81	10.86	10.91	10.96	11.01	11.06	11.11

NMOT: 辐照度 irradiance 800W/m², 环境温度 environment temperature 20°C, 风速 wind speed 1m/s

机械性能 MECHANICAL SPECIFICATIONS

组件尺寸 External Dimension (L×W×H)	2279mm×1134mm×30mm
组件重量 Weight	31.5kg
电池 Number of Cells	144(6×24)/16BB
正面玻璃规格 Front Glass	2.0mm 减反射镀膜热增强玻璃 2.0mm AR-coating heat-strengthened glass
背面玻璃规格 Rear Glass	2.0mm 热增强玻璃 2.0mm heat-strengthened glass
边框 Frame	防积灰边框 Dust accumulation prevention
接线盒防护等级 Junction Box	IP68
线缆规格 Output Cables	4mm², 300mm或客户定制 4mm², 300mm or customized length
连接器 Connector	MC4兼容 MC4 Compatible

工作条件 APPLICATION CONDITIONS

最大系统电压 Maximum System Voltage	DC1500V(IEC)
最大保险丝额定电流 Maximum Series Fuse Rating	25A
工作温度范围 Operating Temperature	-40°C~+85°C
机械载荷 Mechanical Load	5400Pa / 2400Pa
冰雹撞击试验 Hail Test	φ25mm冰雹, 从1m的距离以23 m/s的速度 25mm diameter hail at 23m/s
应用等级 Application Rating	Class A


温度系数 TEMP CHARACTERISTICS

电池额定工作温度 Nominal Module Operating Temperature (NMOT)	42±2°C
功率温度系数 Temperature Coefficient of Pmax	-0.29%/°C
电压温度系数 Temperature Coefficient of Voc	-0.25%/°C
电流温度系数 Temperature Coefficient of ISC	0.045%/°C


包装 PACKING CONFIGURATION

每托数量 Pieces per Pallet	37片/pcs
包装尺寸 Packaging box Size	2335×1145×1260mm
40HC	740片/pcs
13m	740片/pcs
17.5m	962片/pcs

组件尺寸 TECHNICAL DRAWING



IV曲线 I-V CURVE



SP-N16/144HG570-600W